

CASSETTE TYPE

AIR CONDITIONING

MODEL : CM,CR/DCCM5



GOLD FIN



3-SPEED FAN



4 WAYS AUTO SWING



SLEEP MODE



TIMER



FILTER



คอมเพรสเซอร์
COMPRESSOR



อะไหล่
SPARE PART



ISO 9001:2015



ISO 14001:2015



ISO 45001:2018



TUV NORD Thailand Ltd.



TUV NORD Thailand Ltd.



TUV NORD Thailand Ltd.



SOCOTEC



มาตรฐานคุณภาพ
ประเทศไทย
TQS



ENERGY STAR



NSC-TIS 11025



Made in Thailand



THAILAND TRUSTED QUALITY



TQS



TQS

CASSETTE TYPE

AIR CONDITIONING



CASSETTE TYPE NUMBER 5

MODEL: DCCM5 / CM, CR



CASSETTE TYPE

INDOOR UNIT MODEL		DCCM5-18	DCCM5-25	DCCM5-30	DCCM5-30	DCCM5-36	DCCM5-36	DCCM5-36	DCCM5-40	DCCM5-40	
AIR FLOW	CFM	600	850	1,000	1,000	1,150	1,150	1,150	1,235	1,235	
POWER SUPPLY	V / Ph / Hz	220/1/50									
FAN	TYPE	SINGLE INLET BACKWARD CURVED CENTRIFUGAL FAN									
	QTY	1	1	1	1	1	1	1	1	1	
MOTOR	TYPE	PERMANENT SPLIT CAPACITY									
	QTY	1	1	1	1	1	1	1	1	1	
CONNECTION	SUCTION INCH	1/2	5/8	5/8	5/8	5/8	5/8	5/8	5/8	5/8	
	LIQUID INCH	1/4	3/8	1/4	1/4	3/8	3/8	3/8	3/8	3/8	
FRONT DIMENSION	WIDTH CM	95.00	95.00	95.00	95.00	95.00	95.00	95.00	95.00	95.00	
	HEIGHT CM	95.00	95.00	95.00	95.00	95.00	95.00	95.00	95.00	95.00	
	DEPTH CM	5.50	5.50	5.50	5.50	5.50	5.50	5.50	5.50	5.50	
APPROX WEIGHT	KG	6.00	6.00	6.00	6.00	6.00	6.00	6.00	6.00	6.00	
UNIT DIMENSION	WIDTH CM	83.00	83.00	83.00	83.00	83.00	83.00	83.00	83.00	83.00	
	HEIGHT CM	83.00	83.00	83.00	83.00	83.00	83.00	83.00	83.00	83.00	
	DEPTH CM	21.00	25.00	25.00	25.00	25.00	25.00	25.00	29.00	25.00	
APPROX UNIT WEIGHT	KG	22.20	25.80	28.00	28.00	28.00	28.00	28.00	30.50	30.50	
OUTDOOR UNIT MODEL		CM-185-A	CM-255-A	CR-305-A	CR-305-3	CR-365-A	CR-365-3	CR-365-3B	CR-405-A	CR-405-3	
COOLING CAPACITY	BTU/HR.	18,562	27,232	32,927	34,079	36,065	36,033	36,582	40,098	40,035	
	WATT	5,300	7,300	8,800	8,800	10,600	10,600	10,600	11,800	11,800	
POWER INPUT	WATT	1,472.00	2,030.00	2,565.00	2,565.00	3,090.00	3,090.00	3,090.00	3,451.30	3,439.20	
SEER	BTU/WATT	13.12	13.65	13.39	14.13	13.12	13.39	13.12	12.67	13.12	
COMPRESSOR	TYPE	ROTARY						SCROLL		ROTARY	
CONDENSER COIL	TYPE	COPPER TUBE AND ALUMINIUM FIN									
REFRIGERANT	TYPE	R32									
POWER SUPPLY	V / Ph / Hz	220/1/50	220/1/50	220/1/50	380/3/50	220/1/50	380/3/50	380/3/50	220/1/50	380/3/50	
MOTOR	TYPE	PERMANENT SPLIT CAPACITY									
CONNECTION	SUCTION INCH	1/2	5/8	5/8	5/8	5/8	5/8	5/8	5/8	5/8	
	LIQUID INCH	1/4	3/8	1/4	1/4	3/8	3/8	3/8	3/8	3/8	
DIMENSION	WIDTH CM	80.50	94.60	98.00	98.00	110.00	110.00	110.00	110.00	110.00	
	HEIGHT CM	55.5	81.00	79.50	79.50	110.50	110.50	110.50	110.50	110.50	
	DEPTH CM	33.00	41.00	39.00	39.00	40.00	40.00	40.00	40.00	40.00	
APPROX WEIGHT	KG	40.00	61.00	67.00	67.00	80.00	80.00	90.00	90.00	90.00	

Note : Cooling capacity base on 27 °C D.B., 19 °C W.B., Air on evaporator coil and 35 °C Ambient air for outdoor unit. Specification subject to change without notice.