

ONE WAY CASSETTE TYPE

AIR CONDITIONING



ONE WAY CASSETTE TYPE [INVERTER]

MODEL: DCO-IV1/CR-IV



MODEL: DCO-IV1



MODEL: CR-IV



คอมเพรสเซอร์
WARRANTY 5



อะไหล่
WARRANTY 2

INVERTER



1 WAY AUTO SWING



TIMER



FILTER



REMOTE

ONE WAY CASSETTE TYPE INVERTER

INDOOR UNIT MODEL			DCO-125-IV1	DCO-185-IV1	DCO-255-IV1	DCO-305-IV1	DCO-305-3IV1
AIR FLOW	CFM		400	600	800	1,000	1,000
POWER SUPPLY	V / Ph / Hz		220/1/50				
FAN	TYPE		CENTRIFUGAL DOUBLE INLET , DOUBLE WIDTH				
	QTY		2	2	2	2	2
MOTOR	TYPE		BLDC MOTOR				
	QTY		1	1	1	1	1
CONNECTION	SUCTION	INCH	1/2	1/2	5/8	5/8	5/8
	LIQUID	INCH	1/4	1/4	1/4	3/8	3/8
DIMENSION	WIDTH	CM	61.50	61.50	61.50	61.50	61.50
	HEIGHT	CM	95.20	95.20	125.20	125.20	125.20
	DEPTH	CM	21.00	25.00	25.00	25.00	25.00
APPROX WEIGHT	KG		30.00	33.00	38.00	41.00	41.00
OUTDOOR UNIT MODEL			CR-125-IV	CR-185-IV	CR-255-IV	CR-305-IV	CR-305-3IV
COOLING CAPACITY	BTU/HR.		12,293	18,936	25,257	30,032	30,053
	WATT		3,600	5,300	7,300	8,800	8,800
POWER INPUT	WATT		1,000	1,472	1,972	2,840	2,840
SEER	BTU/WATT		17.40	17.78	17.20	16.75	16.99
COMPRESSOR	TYPE		TWIN ROTARY				
CONDENSER COIL	TYPE		COPPER TUBE AND ALUMINIUM FIN				
REFRIGERANT	TYPE		R32				
POWER SUPPLY	V / Ph / Hz		220/1/50				
MOTOR	TYPE		PERMANENT SPLIT CAPACITY				
CONNECTION	SUCTION	INCH	1/2	1/2	5/8	5/8	5/8
	LIQUID	INCH	1/4	1/4	1/4	3/8	3/8
DIMENSION	WIDTH	CM	85.00	95.00	98.00	98.00	98.00
	HEIGHT	CM	54.50	69.50	79.50	79.50	79.50
	DEPTH	CM	28.50	37.00	39.00	39.00	39.00
APPROX WEIGHT	KG		32.00	42.00	55.00	57.00	61.00



Note : Cooling capacity base on 27 °C D.B., 19 °C W.B., Air on evaporator coil and 35 °C Ambient air for outdoor unit. Specification subject to change without notice.

ONE WAY CASSETTE TYPE

AIR CONDITIONING



ONE WAY CASSETTE TYPE [INVERTER]

MODEL: DCO-IV1/CR-IV



MODEL: DCO-IV1



MODEL: CR-IV



คอมเพรสเซอร์
WARRANTY 5

อะไหล่
WARRANTY 2

INVERTER



1 WAY AUTO SWING



TIMER



FILTER



REMOTE

ONE WAY CASSETTE TYPE INVERTER

INDOOR UNIT MODEL			DCO-335-IV1	DCO-335-3IV1	DCO-365-IV1	DCO-365-3IV1	DCO-405-IV1	DCO-405-3IV1
AIR FLOW	CFM		1,100	1,100	1,200	1,200	1,350	1,350
POWER SUPPLY	V / Ph / Hz		220/1/50					
FAN	TYPE		CENTRIFUGAL DOUBLE INLET , DOUBLE WIDTH					
	QTY		4	4	4	4	4	4
MOTOR	TYPE		BLDC MOTOR			AC MOTOR		
	QTY		1	1	1	1	1	1
CONNECTION	SUCTION	INCH	5/8	5/8	5/8	5/8	5/8	5/8
	LIQUID	INCH	3/8	3/8	3/8	3/8	3/8	3/8
DIMENSION	WIDTH	CM	61.50	61.50	61.50	61.50	61.50	61.50
	HEIGHT	CM	125.20	125.50	155.20	155.20	155.20	155.20
	DEPTH	CM	25.00	25.00	25.00	25.00	25.00	25.00
APPROX WEIGHT	KG		43.00	43.00	54.00	54.00	54.00	54.00
OUTDOOR UNIT MODEL			CR-335-IV	CR-335-3IV	CR-365-IV	CR-365-3IV	CR-405-IV	CR-405-3IV
COOLING CAPACITY	BTU/HR.		32,508	32,897	36,732	37,321	40,101	40,345
	WATT		9,500	9,500	10,600	10,600	11,800	11,800
POWER INPUT	WATT		3,060	3,060	3,420	3,420	3,810	3,810
SEER	BTU/WATT		16.79	16.14	16.82	16.72	16.04	16.51
COMPRESSOR	TYPE		TWIN ROTARY					
CONDENSER COIL	TYPE		COPPER TUBE AND ALUMINIUM FIN					
REFRIGERANT	TYPE		R32					
POWER SUPPLY	V / Ph / Hz		220/1/50	380/3/50	220/1/50	380/3/50	220/1/50	380/3/50
MOTOR	TYPE		PERMANENT SPLIT CAPACITY					
CONNECTION	SUCTION	INCH	5/8	5/8	5/8	5/8	5/8	5/8
	LIQUID	INCH	3/8	3/8	3/8	3/8	3/8	3/8
DIMENSION	WIDTH	CM	98.00	98.00	98.00	98.00	110.00	110.00
	HEIGHT	CM	79.50	79.50	79.50	79.50	110.50	110.50
	DEPTH	CM	39.00	39.00	39.00	36.00	40.00	40.00
APPROX WEIGHT	KG		57.00	61.00	57.00	61.00	77.00	80.00



Note : Cooling capacity base on 27 °C D.B., 19 °C W.B., Air on evaporator coil and 35 °C Ambient air for outdoor unit. Specification subject to change without notice.