

# CONCEALED TYPE

## AIR CONDITIONING



### CONCEALED TYPE

MODEL: DHD / CR



MODEL: DHD



MODEL: DHD



MODEL: CR



SERVICE VALVE



MAGNETIC



POWDER COATING SYSTEM

INDOOR UNIT MODEL			DHD-400	DHD-600	DHD-800	DHD-1000	DHD-1000	DHD-1100	DHD-1100	DHD-1200	
AIR FLOW	CFM		400	600	800	1,000	1,000	1,100	1,100	1,200	
POWER SUPPLY	V / Ph / Hz		220/ 1 / 50								
FAN	TYPE		CENTRIGUL DOUBLE INLET, DOUBLE WIDTH								
	QTY		2	2	2	4	4	4	4	4	
MOTOR	TYPE		PERMANENT SPLIT CAPACITOR								
	QTY		1	1	1	1	1	1	1	2	
CONNECTION	SUCTION	INCH	1/2	1/2	5/8	5/8	5/8	5/8	5/8	5/8	
	LIQUID	INCH	1/4	1/4	1/4	1/4	1/4	3/8	3/8	3/8	
DIMENSION	WIDTH	CM	92.00	97.00	122.20	128.00	128.00	128.00	128.00	174.00	
	HEIGHT	CM	21.00	23.00	23.40	25.00	25.00	25.00	25.00	25.00	
	DEPTH	CM	48.00	50.50	50.50	53.00	53.00	53.00	53.00	50.50	
OUTDOOR UNIT MODEL			CR-12	CR-18	CR-25	CR-30	CR-30-3	CR-33	CR-33-3	CR-36	
COOLING CAPACITY	BTU/HR.		13,000	18,100	25,000	30,000	30,000	32,400	32,400	36,200	
	WATT		3,800	5,300	7,300	8,800	8,800	9,500	9,500	10,600	
POWER INPUT	WATT		1,220	1,710	2,030	2,840	2,840	3,060	3,060	3,410	
SEER	BTU/WATT		10.58	10.58	10.58	10.58	10.58	10.58	10.58	10.58	
COMPRESSOR	TYPE		ROTARY								
CONDENSER COIL	TYPE		COPPER TUBE AND ALUMINIUM FIN								
REFRIGERANT	TYPE		R32								
POWER SUPPLY	V / Ph / Hz		220 /1/50	220 /1/50	220 /1/50	220 /1/50	380 /3 / 50	220/1/50	380/3/50	220/1/50	
MOTOR	TYPE		PERMANENT SPLIT CAPACITOR								
CONNECTION	SUCTION	INCH	1/2	1/2	5/8	5/8	5/8	5/8	5/8	5/8	
	LIQUID	INCH	1/4	1/4	1/4	1/4	1/4	3/8	3/8	3/8	
DIMENSION	WIDTH	CM	85.00	95.00	95.00	95.00	95.00	95.00	95.00	98.00	
	HEIGHT	CM	54.50	69.50	69.50	69.50	69.50	69.50	69.50	79.50	
	DEPTH	CM	28.50	37.00	37.00	37.00	37.00	37.00	37.00	39.00	
APPROX WEIGHT	KG		36.00	55.00	56.00	62.00	62.00	62.00	62.00	70.00	



Note : Cooling capacity base on 27 °C D.B., 19 °C W.B., Air on evaporator coil and 35 °C Ambient air for outdoor unit.  
Specification subject to change without notice.

# CONCEALED TYPE

## AIR CONDITIONING




### CONCEALED TYPE

MODEL: DHD / CR



MODEL: DHD

MODEL: DHD



MODEL: CR



SERVICE VALVE



MAGNETIC



POWDER COATING SYSTEM

INDOOR UNIT MODEL			DHD-1200	DHD-1400	DHD-1400	DHD-1500	DHD-1600	DHD-2000
AIR FLOW	CFM		1,200	1,400	1,400	1,500	1,600	2,000
POWER SUPPLY	V / Ph / Hz		220/1/50					
FAN	TYPE		CENTRIFUGAL DOUBLE INLET , DOUBLE WIDTH					
	QTY		4	4	4	4	4	4
MOTOR	TYPE		PERMANENT SPLIT CAPACITOR					
	QTY		2	2	2	2	2	2
CONNECTION	SUCTION	INCH	5/8	5/8	5/8	5/8	5/8	3/4
	LIQUID	INCH	3/8	3/8	3/8	3/8	3/8	3/8
DIMENSION	WIDTH	CM	174.00	186.50	186.50	153.00	186.00	186.50
	HEIGHT	CM	25.00	25.00	25.00	23.00	25.00	25.00
	DEPTH	CM	50.50	54.70	54.70	50.50	55.00	54.70
OUTDOOR UNIT MODEL			CR-36-3	CR-40	CR-40-3	CR 45	CR 48	CR 60
COOLING CAPACITY	BTU/HR.		36,200	40,300	40,300	45,000	48,000	60,900
	WATT		10,600	11,800	11,800	13,200	14,100	17,600
POWER INPUT	WATT		3,410	3,810	3,810	4,400	4,700	6,160
SEER	BTU/WATT		10.58	10.58	10.58	10.24	10.24	9.89
COMPRESSOR	TYPE		ROTARY			SCROLL		
CONDENSER COIL	TYPE		COPPER TUBE AND ALUMINIUM FIN					
REFRIGERANT	TYPE		R32					
POWER SUPPLY	V / Ph / Hz		380/3/50	220/1/50	380/3/50	380 / 3 / 50	380 / 3 / 50	380 / 3 / 50
MOTOR	TYPE		PERMANENT SPLIT CAPACITOR					
CONNECTION	SUCTION	INCH	5/8	5/8	5/8	5/8	5/8	3/4
	LIQUID	INCH	3/8	3/8	3/8	3/8	3/8	3/8
DIMENSION	WIDTH	CM	98.00	98.00	98.00	110.00	110.00	110.00
	HEIGHT	CM	79.50	79.50	79.50	110.50	110.50	110.50
	DEPTH	CM	39.00	39.00	39.00	40.00	40.00	40.00
APPROX WEIGHT	KG		70.00	75.00	75.00	85.00	85.00	95.00



Note : Cooling capacity base on 27 °C D.B., 19 °C W.B., Air on evaporator coil and 35 °C Ambient air for outdoor unit.  
Specification subject to change without notice.